



10VIEW

Preliminary technical brochure



ITALIAN DESIGN
SOFTWARE CUSTOMIZATION
SAFETY CARE
OPERATOR ORIENTED

TECHNICAL FEATURES

Operating voltage: 6 – 32 Vdc, protected against reverse polarity

Operating temperature: -30°C +85°C

Sealing: IP67

CPU: Arm® Cortex®-A9

RAM: 5MB

FLASH: 32MB

HW Watchdog

DISPLAY: COLOR TFT 10,1" 1024X600 1000NITS IPS TECHNOLOGY

CAPACITIVE TOUCHSCREEN

5 LED indicator or 5 silicon pushbutton

3 CANBUS ports

1 USB port

1 LINBUS port

1 UART TTL (for debug)

22 DIGITAL INPUT(analogici)

8 RESISTIVE (2 INPUT for PT100/1000)...

4 frequency INPUT (0-10KHz, PICKUP, PNP, NPN)

2 IN 4-20mA

2 IN 0-10V

4 HSD OUTPUT 1A

1 Vout for external senso (5V o 10V) (+ e GND)

2 video INPUT

1 buzzer 105dB @30cm

1 internal RTC (real time clock)

Programmable in C languages with API or with eDASH3K

CAN bootloader for FW upgrade



Strumentazione analogica-digitale,
centraline elettroniche e spie

Analog-Digital instruments,
Electronic Control Board & Indicators

ITALIAN DESIGN
SOFTWARE CUSTOMIZATION
SAFETY CARE
OPERATOR ORIENTED

AMA INSTRUMENTS

Via Repubblica, 7
41011 Campogalliano, MO (Italy)
Tel. 0522 636331 - Fax 0522 695753
www.ama.it - ama@ama.it

Headquarter:

AMA S.p.a.

Via Giacomo Puccini, 28
42018 San MArtino in Rio (RE) Italy
Tel. +39 0522 6369 (10 linee r.a.) - Fax +39 0522 695753
www.ama.it - ama@ama.it

AZIENDA CON SISTEMA DI GESTIONE
PER LA QUALITÀ CERTIFICATO DA DNV
= UNI EN ISO 9001:2008 =